

Self-Contained High-Pressure Mini Lift Bag Kit

Standard kit includes:

4 high pressure lifting bags 6", 9", (2) x12"



Cylinder, regulator, 10' hose, & air transfer fitting



air transfer fitting for refilling the cylinder

(2) 10' controller hoses with inline pressure relief and shut-off + (1) wye adapter



Pelican® #1600 waterproof case also included

Bags can be used individually or simultaneously. Use for quick, non-technical rescue or easy manipulation of heavy objects. Can be used to pop open jammed doors, spread parallel rodiron handrail bars, free animals (or persons) if trapped under heavy objects, as well as many other simple scenarios encountered by law enforcement personnel, lifeguards, vehicle service technicians, etc.

(*Note-for demo purposes only)

Lift height in this demo (RIGHT) was approx. 2-3". Proper lateral support and cribbing should be used prior to lifting large, heavy objects in order to prevent lateral shift

- Stack maximum of two bags to gain additional lift height
- Stack bags side by side to gain additional weight lifting power



(SAE SPECS) Technical data - Heavy Lift Air Bags				
USA Specs		SLK 1, 1/2, 8	SLK 3, 5/5	SLK 6, 8/6
Item number	#	77973	77974	77975
Size - deflated	inch	6X6	9X9	12X12
Thickness	Inches	1.1"	1.1"	1.1"
*Max lift height	Inches	2.7"	5.1"	5.9"
*Max Load	US Tons	1.1	3.1	6.4
Bag weight	Lbs	1.32	2.8	5.3
Max. pressure	PSI	116	116	116
Test pressure	PSI	174	174	174
Burst pressure	PSI	464	464	464
Volume	cu./ft.	.18	.53	1.48

Additional Information & Specifications

